

**PRODUCT
SELECTION
GUIDE**

NAME (completing form): _____

PHONE #: _____ DATE _____

END USER: _____

SITE/AREA: _____

1. Application (Type of building/place/industry they will be used in): _____

2. Environment (check all that apply): inside outside wet oily dirty icy acidic other _____

3. Footwear: heeled dress shoes all flat soled work shoes barefoot other _____

4. Traffic: light foot traffic heavy foot traffic vehicle traffic other _____

5. Preferred method of installation: mechanical fasteners adhesive weld other _____

6. Cleaning process/practice: _____

7. Substrate: _____



open grating



wood



solid metal




concrete



Grip Strut® other (describe above) _____

Step Covers



PROFILE

Standard 90° 1" (25 mm)

Bull Nose (less common) 1" (25 mm)

QUANTITY _____

SIZE OF STEP: (not size of cover):

Width (A) _____ x Depth (B) _____

GRIT SIZE / GRADE

(from most to least common)

- Let Safeguard Recommend
- Coarse (Industrial)
- Extra Coarse (Offshore)
- Fine (Commercial)
- Extra Fine (Residential)
- Super Fine (Barefoot)
- Super Coarse (Xtreme™)

BASE MATERIAL

(from most to least common)

- Let Safeguard Recommend
- 1/8 in. Pultruded Fiberglass (FRP)
- Galvanized Steel – 18 gauge (1.2 mm) G90
- Stainless Steel – 18 gauge (1.2 mm) #316


INSTALLATION

- Include predrilled holes:
 - Standard Slotted for grating
- Adhesive - Sikaflex 252
- Other _____

COLORS AND MARKINGS (see color options)

Color _____
Two-Tone nosing color _____
Message / Logo _____

Walkway Covers



QUANTITY _____

SIZE OF AREA: (not size of cover)

Width (A) _____ x Depth (B) _____

GRIT SIZE / GRADE

(from most to least common)

- Let Safeguard Recommend
- Coarse (Industrial)
- Extra Coarse (Offshore)
- Fine (Commercial)
- Extra Fine (Residential)
- Super Fine (Barefoot)
- Super Coarse (Xtreme™)

BASE MATERIAL

(from most to least common)

- Let Safeguard Recommend
- 1/8 in. Pultruded Fiberglass (FRP)
- Galvanized Steel – 18 gauge (1.2 mm) G90
- Stainless Steel – 18 gauge (1.2 mm) #316
- 1 mm Molded Fiberglass (FRP)
- Roll-Traction®
- Vinyl (Flexible PVC with PSA/peel & stick)


INSTALLATION

- Include predrilled holes:
 - Standard Slotted for grating
- Adhesive - Sikaflex 252
- Other _____

COLORS AND MARKINGS (see color options)

Color _____
Two-Tone nosing color _____
Message / Logo _____

Ladder Rung Covers



Channel Round

QUANTITY _____

SIZE OF RUNG: (not size of cover)

Width (A) _____ x Diameter (B) _____

GRIT SIZE / GRADE

(from most to least common)

- Let Safeguard Recommend
- Coarse (Industrial)
- Extra Coarse (Offshore)
- Fine (Commercial)
- Extra Fine (Residential)
- Other _____

BASE MATERIAL

(from most to least common)

- Let Safeguard Recommend
- 1/8 in. Pultruded Fiberglass (FRP)
- Galvanized Steel – 18 gauge (1.2 mm) G90
- Stainless Steel – 18 gauge (1.2 mm) #316

INSTALLATION

- Include adhesive - Sikaflex 252
- Bare edges for tack welding
- Other _____

COLORS AND MARKINGS (see color options)

Color _____
Two-Tone nosing color _____
Message / Logo _____

330-995-5200 | 800-989-1695
Fax 330-995-5201
info@safeguard-technology.com
www.safeguard-technology.com